

Description

Length: 2-3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1677D10W24N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-576-5963
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	157170, Plastic / Rubr Straps / Rope / Cord / Strip

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1677D10W24N Specifications

Overall Length:	2.758 Inches Nominal
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.040 Inches Nominal
Distance Between Mounting Hole Centers:	2.320 Inches Nominal
Cushioning Material:	Rubber, Synthetic
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	0.610 Inches Minimum And 0.640 Inches Maximum
Inside Diameter/arch Length:	1.485 Inches Minimum And 1.515 Inches Maximum
Material:	Aluminum Alloy
Material:	Aluminum Alloy
Style Designator:	Saddle Arch

How to Order

Order this cushioned retaining strap from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D10W24N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.