

Description

Length: 2-29/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1677D10W26N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-131-5651
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	157170, Plastic / Rubr Straps / Rope / Cord / Strip



* See page 2 for technical characteristics

P/N NAS1677D10W26N Specifications

Overall Length:	2.853 Inches Minimum And 2.913 Inches Maximum
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.051 Inches Nominal
Distance Between Mounting Hole Centers:	2.415 Inches Minimum And 2.475 Inches Maximum
Cushioning Material:	Rubber, Synthetic, Ams 3209
Cushion:	Included
Mounting Pad:	Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	0.753 Inches Minimum And 0.783 Inches Maximum
Inside Diameter/arch Length:	1.610 Inches Minimum And 1.640 Inches Maximum
Special Features:	Rectangular In Shape; Wedge Included
Material:	Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4 Or Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T42
Material:	Aluminum Alloy 2024 And Aluminum Alloy 1230 Or Aluminum Alloy 2024 And Aluminum Alloy 1230
Style Designator:	Saddle Arch
Specification/standard Data:	80205-nas1677 Professional/industrial Association Standard

How to Order

Order this cushioned retaining strap from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D10W26N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.