

P/N NAS1677D10W43N

Description

Length: 3-15/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1677D10W43N
Minimum Qty (MOQ): 5 EA

NSN: 5340-01-081-9742

Schedule B: 7616.10.9090

ECCN: 9A991

National Motor Freight: 095190, Hardware, Noi Sub 9



^{*} See page 2 for technical characteristics

P/N NAS1677D10W43N Specifications

| Overall Length: | 3.946 Inches Nominal |
|---|---|
| Overall Width: | 0.500 Inches Nominal |
| Material Thickness: | 0.051 Inches Nominal |
| Distance Between Mounting Hole Centers: | 3.508 Inches Nominal |
| Cushioning Material: | Rubber, Synthetic, Ams 3209 |
| Cushion: | Included |
| Mounting Pad: | Not Included |
| Mounting Hole Size: | 0.204 Inches Nominal |
| Distance Between Base And Inside Of Arch: | 0.768 Inches Nominal |
| Inside Diameter/arch Length: | 2.673 Inches Minimum And 2.703 Inches Maximum |
| Special Features: | Rectangular Shape |
| Material: | Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4 Or Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T42 |
| Material: | Aluminum Alloy 2024 And Aluminum Alloy 1230 Or Aluminum Alloy 2024 And Aluminum Alloy 1230 |
| Style Designator: | Saddle Arch |
| Specification/standard Data: | 80205-nas1677 Professional/industrial Association Standard |

How to Order

Order this cushioned retaining strap from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D10W43N and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.