

Description

Length: 2-1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1677D12W20N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-615-1813
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	157170, Plastic / Rubr Straps / Rope / Cord / Strip

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1677D12W20N Specifications

Overall Length:	2.50 Inches Nominal
Overall Width:	0.47 Inches Minimum And 0.50 Inches Maximum
Material Thickness:	0.041 Inches Minimum And 0.061 Inches Maximum
End Item Identification:	F/a-18 E/f
Cushioning Material:	Rubber, Synthetic, Ams 3209
Cushion:	Included
Mounting Pad:	Not Included
Distance Between Base And Inside Of Arch:	0.735 Inches Minimum And 0.765 Inches Maximum
Inside Diameter/arch Length:	1.235 Inches Minimum And 1.265 Inches Maximum
Part Name Assigned By Controlling Agency:	Strap, Retaining
Material:	Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4 Or Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T42
Material:	Aluminum Alloy 2024 And Aluminum Alloy 1230 Or Aluminum Alloy 2024 And Aluminum Alloy 1230
Style Designator:	Saddle Arch
Specification/standard Data:	80205-nas1677d12w20n Professional/industrial Association Standard

How to Order

Order this cushioned retaining strap from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D12W20N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.