

# **P/N NAS1677D12W29N**

## **Description**

Cushioned Retaining Strap part number

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1677D12W29N

Minimum Qty (MOQ): 5 EA

NSN: 5340-01-607-6400

Schedule B: 7616.10.1000

ECCN: 9A991

National Motor Freight: 157170, Plastic / Rubr Straps / Rope / Cord / Strip



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1677D12W29N Specifications

Overall Width:	0.500 Inches Nominal
Material Thickness:	0.051 Inches Nominal
Distance Between Mounting Hole Centers:	2.603 Inches Minimum And 2.663 Inches Maximum
End Item Identification:	F/a-18 E/f
Cushioning Material:	Rubber, Synthetic
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	0.735 Inches Minimum And 0.765 Inches Maximum
Inside Diameter/arch Length:	1.798 Inches Minimum And 1.828 Inches Maximum
Part Name Assigned By Controlling Agency:	Strap, Retaining-cushioned, Rectangular, Two Piece
Special Features:	Includes Wedges
Material:	Aluminum Alloy, Qq-a-200/5, Alloy 5086
Material:	Aluminum Alloy 5086
Style Designator:	Saddle Arch

### **How to Order**

Order this cushioned retaining strap from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D12W29N">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D12W29N</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.