

Description

Length: 3-25/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1677D15W40N
Minimum Qty (MOQ):	5 EA
NSN:	5340-00-480-8780
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	157170, Plastic / Rubr Straps / Rope / Cord / Strip



P/N NAS1677D15W40N Specifications

Overall Length:	3.728 Inches Minimum And 3.788 Inches Maximum
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.051 Inches Nominal
Distance Between Mounting Hole Centers:	3.290 Inches Minimum And 3.350 Inches Maximum
Cushioning Material:	Rubber,synthetic Ams 3209
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	1.066 Inches Minimum And 1.096 Inches Maximum
Inside Diameter/arch Length:	2.485 Inches Minimum And 2.515 Inches Maximum
Special Features:	Rectangular Shape
Material:	Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4 Or Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T42
Material:	Aluminum Alloy 2024 And Aluminum Alloy 1230 Or Aluminum Alloy 2024 And Aluminum Alloy 1230
Style Designator:	Saddle Arch
Specification/standard Data:	80205-nas1677 Professional/industrial Association Standard

How to Order

Order this cushioned retaining strap from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D15W40N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.