

Description

Length: 4-23/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1677D15W55N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-044-0985
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	157170, Plastic / Rubr Straps / Rope / Cord / Strip

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1677D15W55N Specifications

Overall Length:	4.666 Inches Minimum And 4.726 Inches Maximum
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.051 Inches Nominal
Distance Between Mounting Hole Centers:	4.228 Inches Minimum And 4.288 Inches Maximum
Cushioning Material:	Rubber, Synthetic, Ams 3209
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	0.456 Inches Nominal
Inside Diameter/arch Length:	3.438 Inches Nominal
Special Features:	Rectangular Shape
Material:	Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4 Or Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T42
Material:	Aluminum Alloy 2024 And Aluminum Alloy 1230 Or Aluminum Alloy 2024 And Aluminum Alloy 1230
Style Designator:	Saddle Arch
Specification/standard Data:	80205-nas1677 Professional/industrial Association Standard

How to Order

Order this cushioned retaining strap from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D15W55N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.