

**Description**

Length: 4-11/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1677D16W55N                                      |
| Minimum Qty (MOQ):      | 5 EA  |
| NSN:                    | 5340-01-119-6478                                    |
| Schedule B:             | 7616.10.9090  |
| ECCN:                   | 9A991   |
| National Motor Freight: | 157170, Plastic / Rubr Straps / Rope / Cord / Strip |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1677D16W55N Specifications

|  |   |
|--|---|
| <b>Overall Length:</b>                           | 4.698 Inches Nominal  |
| <b>Overall Width:</b>                            | 0.500 Inches Nominal  |
| <b>Material Thickness:</b>                       | 0.051 Inches Nominal  |
| <b>Distance Between Mounting Hole Centers:</b>   | 4.230 Inches Minimum And 4.290 Inches Maximum   |
| <b>Cushioning Material:</b>                      | Rubber, Synthetic, Ams 3209   |
| <b>Cushion:</b>                                  | Included  |
| <b>Mounting Pad:</b>                             | Not Included  |
| <b>Mounting Hole Size:</b>                       | 0.204 Inches Nominal  |
| <b>Distance Between Base And Inside Of Arch:</b> | 1.128 Inches Minimum And 1.158 Inches Maximum   |
| <b>Inside Diameter/arch Length:</b>              | 3.425 Inches Minimum And 3.455 Inches Maximum   |
| <b>Special Features:</b>                         | Rectangular Shape   |
| <b>Material:</b>                                 | Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4 Or Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T42 |
| <b>Material:</b>                                 | Aluminum Alloy 2024 And Aluminum Alloy 1230 Or Aluminum Alloy 2024 And Aluminum Alloy 1230              |
| <b>Style Designator:</b>                         | Saddle Arch   |
| <b>Specification/standard Data:</b>              | 80205-nas1677 Professional/industrial Association Standard  |

## How to Order

Order this cushioned retaining strap from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D16W55N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.