

P/N NAS1677D16W59N

Description

Length: 4-15/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1677D16W59N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-336-9611
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi



^{*} See page 2 for technical characteristics

P/N NAS1677D16W59N Specifications

Overall Length:	4.946 Inches Nominal
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.051 Inches Nominal
Distance Between Mounting Hole Centers:	4.508 Inches Nominal
Cushioning Material:	Rubber, Synthetic
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	0.885 Inches Minimum And 1.015 Inches Maximum
Inside Diameter/arch Length:	3.673 Inches Minimum And 3.703 Inches Maximum
Special Features:	Rectangular Shape
Material:	Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4 Or Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T42
Material:	Aluminum Alloy 2024 And Aluminum Alloy 1230 Or Aluminum Alloy 2024 And Aluminum Alloy 1230
Style Designator:	Saddle Arch
Specification/standard Data:	80205-nas1677 Professional/industrial Association Standard

How to Order

Order this cushioned retaining strap from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D16W59N and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.