

**Description**

Length: 4-11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1677D20W49N
Minimum Qty (MOQ):	5 EA
NSN:	5340-00-480-8802
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013120, Aluminum Article Noi Sub 6



\* See page 2 for technical characteristics

# P/N NAS1677D20W49N Specifications

Overall Length:	4.290 Inches Minimum And 4.350 Inches Maximum
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.051 Inches Nominal
Distance Between Mounting Hole Centers:	3.852 Inches Minimum And 3.912 Inches Maximum
Cushioning Material:	Rubber, Synthetic, Ams 3209
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	1.378 Inches Minimum And 1.408 Inches Maximum
Inside Diameter/arch Length:	3.047 Inches Minimum And 3.077 Inches Maximum
Special Features:	Rectangular Shape
Material:	Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4 Or Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T42
Material:	Aluminum Alloy 2024 And Aluminum Alloy 1230 Or Aluminum Alloy 2024 And Aluminum Alloy 1230
Style Designator:	Saddle Arch
Specification/standard Data:	80205-nas1677 Professional/industrial Association Standard

## How to Order

Order this cushioned retaining strap from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D20W49N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.