

Description

Length: 4-1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1677D24W52N |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-00-446-9296 |
| Schedule B: | 7616.10.1000 |
| ECCN: | 9A991 |
| National Motor Freight: | 157170, Plastic / Rubr Straps / Rope / Cord / Strip |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1677D24W52N Specifications

| | |
|--|--|
| Overall Length: | 4.508 Inches Nominal |
| Overall Width: | 0.500 Inches Nominal |
| Material Thickness: | 0.051 Inches Nominal |
| Distance Between Mounting Hole Centers: | 4.070 Inches Nominal |
| Cushioning Material: | Rubber, Synthetic, Ams 3209 |
| Cushion: | Included |
| Mounting Pad: | Not Included |
| Mounting Hole Size: | 0.204 Inches Nominal |
| Distance Between Base And Inside Of Arch: | 1.645 Inches Nominal |
| Inside Diameter/arch Length: | 3.250 Inches Nominal |
| Special Features: | Rectangular Shape |
| Material: | Aluminum Alloy, Qq-a-250/5 |
| Material: | Aluminum Alloy 2024 |
| Style Designator: | Saddle Arch |
| Specification/standard Data: | 80205-nas1677 Professional/industrial Association Standard |

How to Order

Order this cushioned retaining strap from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D24W52N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.