

**Description**

Length: 3-3/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1677D28W40N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-144-5870
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	013120, Aluminum Article Noi Sub 6

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1677D28W40N Specifications

<b>Overall Length:</b>	3.758 Inches Nominal
<b>Overall Width:</b>	0.500 Inches Nominal
<b>Material Thickness:</b>	0.051 Inches Nominal
<b>Distance Between Mounting Hole Centers:</b>	3.290 Inches Minimum And 3.350 Inches Maximum
<b>Cushioning Material:</b>	Rubber, Synthetic, Ams 3209
<b>Cushion:</b>	Included
<b>Mounting Pad:</b>	Not Included
<b>Mounting Hole Size:</b>	0.204 Inches Nominal
<b>Distance Between Base And Inside Of Arch:</b>	1.893 Inches Nominal
<b>Inside Diameter/arch Length:</b>	2.485 Inches Minimum And 2.515 Inches Maximum
<b>Special Features:</b>	Rectangular Shape
<b>Material:</b>	Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4 Or Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T42
<b>Material:</b>	Aluminum Alloy 2024 And Aluminum Alloy 1230 Or Aluminum Alloy 2024 And Aluminum Alloy 1230
<b>Style Designator:</b>	Saddle Arch
<b>Specification/standard Data:</b>	80205-nas1677 Professional/industrial Association Standard

## How to Order

Order this cushioned retaining strap from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D28W40N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.