



Military-Fasteners.com

P/N NAS1677D32W37N

## Description

Length: 3-39/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1677D32W37N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-607-7322
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	157170, Plastic / Rubr Straps / Rope / Cord / Strip



\* See page 2 for technical characteristics

# P/N NAS1677D32W37N Specifications

Overall Length:	3.5255 Inches Minimum And 3.6155 Inches Maximum
Overall Width:	0.50 Inches Nominal
Material Thickness:	0.051 Inches Nominal
Distance Between Mounting Hole Centers:	3.0875 Inches Minimum And 3.1775 Inches Maximum
End Item Identification:	F/a-18 E/f
Cushioning Material:	Rubber, Synthetic, Ams 3209
Cushion:	Included
Mounting Pad:	Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	1.985 Inches Minimum And 2.015 Inches Maximum
Inside Diameter/arch Length:	2.2975 Inches Minimum And 2.3275 Inches Maximum
Material:	Aluminum Alloy, 2024, T4
Material:	Aluminum Alloy 2024
Style Designator:	Straight Arch

## How to Order

Order this cushioned retaining strap from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D32W37N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.