

**Description**

Length: 2-"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1677D9W22N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-511-6905
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1677D9W22N Specifications

<b>Overall Length:</b>	2.000 Inches Nominal
<b>Overall Width:</b>	0.500 Inches Nominal
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>Distance Between Mounting Hole Centers:</b>	1.353 Inches Minimum And 1.413 Inches Maximum
<b>End Item Identification:</b>	F18 E/f
<b>Cushioning Material:</b>	Rubber, Synthetic, Ams 3209
<b>Cushion:</b>	Included
<b>Mounting Pad:</b>	Not Included
<b>Mounting Hole Size:</b>	0.204 Inches Nominal
<b>Distance Between Base And Inside Of Arch:</b>	1.360 Inches Minimum And 1.390 Inches Maximum
<b>Inside Diameter/arch Length:</b>	0.548 Inches Minimum And 0.578 Inches Maximum
<b>Criticality Code Justification:</b>	Agav
<b>Part Name Assigned By Controlling Agency:</b>	Strap,retaining-cushioned,rectangular,two Piece
<b>Material:</b>	Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4
<b>Material:</b>	Aluminum Alloy 2024 And Aluminum Alloy 1230
<b>Style Designator:</b>	Saddle Arch

## How to Order

Order this cushioned retaining strap from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D9W22N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.