

Description

Length: 2-"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1677D9W22N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-511-6905
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1677D9W22N Specifications

Overall Length:	2.000 Inches Nominal
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Distance Between Mounting Hole Centers:	1.353 Inches Minimum And 1.413 Inches Maximum
End Item Identification:	F18 E/f
Cushioning Material:	Rubber, Synthetic, Ams 3209
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	1.360 Inches Minimum And 1.390 Inches Maximum
Inside Diameter/arch Length:	0.548 Inches Minimum And 0.578 Inches Maximum
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Strap,retaining-cushioned,rectangular,two Piece
Material:	Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4
Material:	Aluminum Alloy 2024 And Aluminum Alloy 1230
Style Designator:	Saddle Arch

How to Order

Order this cushioned retaining strap from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D9W22N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.