

P/N NAS1712C13-23N

Description

Diameter: 13/64", steel comp 302 band or steel comp 321 band

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS1712C1323N

Minimum Qty (MOQ): 5 EA

NSN: 5340-01-580-9032

Schedule B: 7318.15.2091

ECCN: 9A991

National Motor Freight: 095190, Hardware, Noi



^{*} See page 2 for technical characteristics

P/N NAS1712C13-23N Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Weather Resistant
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.128 Inches Nominal
Loop Width:	0.798 Inches Minimum And 0.828 Inches Maximum
Loop Length:	1.423 Inches Minimum And 1.453 Inches Maximum
Distance From Loop Center To Tongue End:	1.347 Inches Nominal
Material:	Rubber Chloroprene Class Cr Cushion
Material:	Steel Comp 302 Band Or Steel Comp 321 Band
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Mil-s-5059 Mil Spec 1st Material Response Band Or Mil-s-6721 Mil Spec 2nd Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Rectangular
Specification/standard Data:	80205-nas1712 Professional/industrial Association Standard

How to Order

Order this loop cushioned clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/NAS1712C13-23N and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/NAS1712C13-23N and selecting the