

Description

Diameter: 13/64", steel comp 302 band or steel comp 321 bandrubber silicone class q cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1712C1632S
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-361-9209
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

P/N NAS1712C16-32S Specifications

Tongue Hole Type:	Round, Unthreaded
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.372 Inches Minimum And 1.432 Inches Maximum
Loop Width:	0.985 Inches Minimum And 1.015 Inches Maximum
Loop Length:	1.985 Inches Minimum And 2.015 Inches Maximum
Distance From Loop Center To Tongue End:	1.621 Inches Minimum And 1.681 Inches Maximum
Material:	Steel Comp 302 Band Or Steel Comp 321 Bandrubber Silicone Class Q Cushion
Material Document And Classification:	Mil-s-5059 Mil Spec 1st Material Response Band Or Mil-s-6721 Mil Spec 2nd Material Response Bandams 3303 Assn Std Single Material Response Cushion
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Ams 3303 Assn Std Single Treatment Response Band
Style Designator:	Rectangular

How to Order

Order this loop cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712C16-32S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.