

Description

Diameter: 7/32", steel corrosion resisting band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1712C2425N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-581-4259
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

P/N NAS1712C24-25N Specifications

Tongue Hole Type:	Round, Unthreaded
Diameter:	0.219 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.000 Inches Nominal
Loop Width:	0.500 Inches Nominal
Loop Length:	2.000 Inches Nominal
Distance From Loop Center To Tongue End:	1.219 Inches Nominal
Special Features:	Cushion Material; Chloroprene Rubber Per Ams 3209
Material:	Rubber Synthetic Cushion
Material:	Steel Corrosion Resisting Band
Material Document And Classification:	Ams 5516 Or Mil-s-5059, Or 321, Per Ams 5510 Or Mil-s-6721 Or 304 Per Ams 5513 Mil Std All Material Responses Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Ams 2700, Method 1 Type 6 Or 7, Class 1 Assn Std All Treatment Responses Band
Style Designator:	Multiple Loop

How to Order

Order this loop cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712C24-25N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.