

Description

Diameter: 7/32", steel corrosion resisting band

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1712C2425N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-581-4259
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi



\* See page 2 for technical characteristics

## P/N NAS1712C24-25N Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Diameter:</b>	0.219 Inches Nominal
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	1.000 Inches Nominal
<b>Loop Width:</b>	0.500 Inches Nominal
<b>Loop Length:</b>	2.000 Inches Nominal
<b>Distance From Loop Center To Tongue End:</b>	1.219 Inches Nominal
<b>Special Features:</b>	Cushion Material; Chloroprene Rubber Per Ams 3209
<b>Material:</b>	Rubber Synthetic Cushion
<b>Material:</b>	Steel Corrosion Resisting Band
<b>Material Document And Classification:</b>	Ams 5516 Or Mil-s-5059, Or 321, Per Ams 5510 Or Mil-s-6721 Or 304 Per Ams 5513 Mil Std All Material Responses Band
<b>Surface Treatment:</b>	Passivate Band
<b>Surface Treatment Document And Classification:</b>	Ams 2700, Method 1 Type 6 Or 7, Class 1 Assn Std All Treatment Responses Band
<b>Style Designator:</b>	Multiple Loop

## How to Order

Order this loop cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712C24-25N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.