

Description

Loop Cushioned Clamp part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1712C413N
Minimum Qty (MOQ):	10 EA
NSN:	5340-01-619-2206
Schedule B:	7318.15.5030
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS1712C4-13N Specifications

Overall Width:	0.50 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.80825 Inches Nominal
Loop Width:	0.235 Inches Minimum And 0.265 Inches Maximum
Loop Length:	0.7975 Inches Minimum And 0.8275 Inches Maximum
Distance From Loop Center To Tongue End:	1.027 Inches Nominal
Part Name Assigned By Controlling Agency:	Clamp,loop,cushioned,rectangular
Special Features:	Cushion Temperature Range Is -40deg F To +212deg F;strap Temperature Range Is -320deg F To +600deg F
Material:	Rubber Chloroprene Class Cr Cushion
Material:	Steel Comp 302 Or Steel Comp 321 Or Steel Comp 304 Band
Material Document And Classification:	Ams3209 National Std/spec Single Material Response Cushion
Material Document And Classification:	Ams5516 National Std/spec 1st Material Response Or Ams5510 National Std/spec 2nd Material Response Or Ams5513 National Std/spec 3rd Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Ams2700,method I,class 4 National Std/spec Single Treatment Response Band
Style Designator:	Rectangular
Specification/standard Data:	80205-nas1712 Professional/industrial Association Standard

How to Order

Order this loop cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712C4-13N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.