

**Description**

Loop Cushioned Clamp part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1712C413N
Minimum Qty (MOQ):	10 EA
NSN:	5340-01-619-2206
Schedule B:	7318.15.5030
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N NAS1712C4-13N Specifications

<b>Overall Width:</b>	0.50 Inches Nominal
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	0.80825 Inches Nominal
<b>Loop Width:</b>	0.235 Inches Minimum And 0.265 Inches Maximum
<b>Loop Length:</b>	0.7975 Inches Minimum And 0.8275 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	1.027 Inches Nominal
<b>Part Name Assigned By Controlling Agency:</b>	Clamp,loop,cushioned,rectangular
<b>Special Features:</b>	Cushion Temperature Range Is -40deg F To +212deg F;strap Temperature Range Is -320deg F To +600deg F
<b>Material:</b>	Rubber Chloroprene Class Cr Cushion
<b>Material:</b>	Steel Comp 302 Or Steel Comp 321 Or Steel Comp 304 Band
<b>Material Document And Classification:</b>	Ams3209 National Std/spec Single Material Response Cushion
<b>Material Document And Classification:</b>	Ams5516 National Std/spec 1st Material Response Or Ams5510 National Std/spec 2nd Material Response Or Ams5513 National Std/spec 3rd Material Response Band
<b>Surface Treatment:</b>	Passivate Band
<b>Surface Treatment Document And Classification:</b>	Ams2700,method I,class 4 National Std/spec Single Treatment Response Band
<b>Style Designator:</b>	Rectangular
<b>Specification/standard Data:</b>	80205-nas1712 Professional/industrial Association Standard

## How to Order

Order this loop cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712C4-13N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.