

Description

Diameter: 3/4", steel comp 302 band or steel comp 321 band or steel comp 304 band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1712C612N
Minimum Qty (MOQ):	10 EA
NSN:	5340-01-485-5848
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	061200, Cable Clamps / Joints Noi

NO IMAGE
AVAILABLE

P/N NAS1712C6-12N Specifications

Tongue Hole Type:	Round, Unthreaded
Overall Width:	0.500 Inches Nominal
Diameter:	0.750 Inches Nominal
Material Thickness:	0.032 Inches Nominal
End Item Identification:	F18 E/f
Center To Center Distance Between Loop And Mounting Hole:	0.747 Inches Minimum And 0.807 Inches Maximum
Loop Width:	0.360 Inches Minimum And 0.390 Inches Maximum
Loop Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Distance From Loop Center To Tongue End:	0.966 Inches Minimum And 1.026 Inches Maximum
Criticality Code Justification:	Agav
Special Features:	Clamp,loop-cushioned,rectangular
Material:	Rubber Chloroprene Class Cr Cushion
Material:	Steel Comp 302 Band Or Steel Comp 321 Band Or Steel Comp 304 Band
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Ams5516 Assn Std 1st Material Response Band Or Ams5510 Assn Std 2nd Material Response Band Or Ams5513 Assn Std 3rd Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35, Type Vi Or Vii Fed Spec Single Treatment Response Band
Style Designator:	Rectangular

How to Order

Order this loop cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712C6-12N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.