

Description

Diameter: 13/64", steel comp 302 band or steel comp 321 band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1712C714S
Minimum Qty (MOQ):	10 EA
NSN:	5340-01-167-9878
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N NAS1712C7-14S Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Corrosion Resistant And Weather Resistant And Oil Resistant
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Fastening Device Type:	Ear Clamped
Center To Center Distance Between Loop And Mounting Hole:	0.839 Inches Nominal
Loop Width:	0.423 Inches Minimum And 0.453 Inches Maximum
Loop Length:	0.860 Inches Minimum And 0.890 Inches Maximum
Distance From Loop Center To Tongue End:	1.058 Inches Nominal
Material:	Rubber Silicone Class Q Cushion
Material:	Steel Comp 302 Band Or Steel Comp 321 Band
Material Document And Classification:	Ams 3303 Assn Std Single Material Response Cushion
Material Document And Classification:	Mil-s-5059 Mil Spec Single Material Response Band Or Mil-s-6721 Mil Spec Single Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Rectangular
Specification/standard Data:	80205-nas1712 Professional/industrial Association Standard

How to Order

Order this loop cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712C7-14S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.