

## P/N NAS1712D10-22T

## **Description**

Diameter: 13/64", plastic polytetrafluoroethylene cushion

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1712D1022T

Minimum Qty (MOQ): 5 EA

NSN: 5340-01-142-9989

Schedule B: 7616.10.9090

ECCN: 9A991

National Motor Freight: 013120, Aluminum Article Noi Sub 6



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1712D10-22T Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Heat
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.090 Inches Nominal
Loop Width:	0.610 Inches Minimum And 0.640 Inches Maximum
Loop Length:	1.360 Inches Minimum And 1.390 Inches Maximum
Distance From Loop Center To Tongue End:	1.309 Inches Nominal
Material:	Aluminum Alloy 2024 Band
Material:	Plastic Polytetrafluoroethylene Cushion
Material Document And Classification:	Ams 3651 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5,condition T4 Or T42 Fed Spec Single Material Response Band
Style Designator:	Rectangular
Specification/standard Data:	80205-nas1712 Professional/industrial Association Standard

### **How to Order**

Order this loop cushioned clamp from our inventory online by visiting <a href="https://military-fasteners.com/clamps/loop+clamps/NAS1712D10-22T">https://military-fasteners.com/clamps/loop+clamps/NAS1712D10-22T</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.