

## P/N NAS1712D11-10N

### **Description**

Diameter: 13/64", rubber chloroprene class cr cushion

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS1712D1110N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-546-7634
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1712D11-10N Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Heat And Oil Resistant And Weather Resistant
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
End Item Identification:	Fwd Fuselag
Center To Center Distance Between Loop And Mounting Hole:	1.152 Inches Nominal
Loop Width:	0.673 Inches Minimum And 0.703 Inches Maximum
Loop Length:	0.063 Inches Nominal
Distance From Loop Center To Tongue End:	1.371 Inches Nominal
Material:	Aluminum Alloy 2024 Band
Material:	Rubber Chloroprene Class Cr Cushion
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5,t4 Fed Spec Single Material Response Band Or Qq-a-250/5,t42 Fed Spec Single Material Response Band
Style Designator:	Rectangular
Specification/standard Data:	80205-nas1712 Professional/industrial Association Standard

## **How to Order**

Order this loop cushioned clamp from our inventory online by visiting <a href="https://military-fasteners.com/clamps/loop+clamps/NAS1712D11-10N">https://military-fasteners.com/clamps/loop+clamps/NAS1712D11-10N</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.