

**Description**

Diameter: 13/64", rubber chloroprene class cr cushion

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1712D116N
Minimum Qty (MOQ):	10 EA
NSN:	5340-01-579-7750
Schedule B:	4016.93.1010
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS1712D11-6N Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Overall Width:</b>	0.500 Inches Nominal
<b>Diameter:</b>	0.204 Inches Nominal
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	0.590 Inches Nominal
<b>Loop Width:</b>	0.673 Inches Minimum And 0.703 Inches Maximum
<b>Loop Length:</b>	0.360 Inches Minimum And 0.390 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	0.809 Inches Nominal
<b>Part Name Assigned By Controlling Agency:</b>	Clamp, Loop, Cushioned, Rectangular
<b>Material:</b>	Aluminum Alloy 2024 Band And Aluminum Alloy 1230 Band
<b>Material:</b>	Rubber Chloroprene Class Cr Cushion
<b>Material Document And Classification:</b>	Ams 3209 Assn Std Single Material Response Cushion
<b>Material Document And Classification:</b>	Ams-qq-250/5 Condition T4 Or T42 Assn Std Single Material Response Band
<b>Style Designator:</b>	Rectangular

## How to Order

Order this loop cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712D11-6N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.