

Description

Diameter: 13/64", rubber chloroprene class cr cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | NAS1712D1215N |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5340-01-511-6888 |
| Schedule B: | 7616.10.1000 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi |

NO IMAGE
AVAILABLE

P/N NAS1712D12-15N Specifications

| | |
|--|---|
| Tongue Hole Type: | Round, Unthreaded |
| Overall Width: | 0.500 Inches Nominal |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.032 Inches Nominal |
| End Item Identification: | F-18 E/f Aircraft |
| Center To Center Distance Between Loop And Mounting Hole: | 0.87075 Inches Nominal |
| Loop Width: | 0.859 Inches Minimum And 0.889 Inches Maximum |
| Loop Length: | 0.9225 Inches Minimum And 0.9525 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.08975 Inches Nominal |
| Criticality Code Justification: | Agav |
| Special Features: | Spec Title - Clamp,loop-cushioned,rectangular |
| Material: | Aluminum Alloy 2024 Band And Aluminum Alloy 1230 Band |
| Material: | Rubber Chloroprene Class Cr Cushion |
| Material Document And Classification: | Ams3209 Assn Std Single Material Response Cushion |
| Material Document And Classification: | Qq-a-250/5 Fed Spec All Material Responses Band |
| Style Designator: | Rectangular |
| Supplementary Features: | Temp Range -- Cushion Minus 40 Deg To Plus 212 Deg F; Strap Minus 320 Deg To Plus 600 Deg F |

How to Order

Order this loop cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712D12-15N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.