

Description

Diameter: 13/64", rubber chloroprene class cr cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | NAS1712D1322N |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-01-543-3841 |
| Schedule B: | 7616.10.1000 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi |

NO IMAGE
AVAILABLE

P/N NAS1712D13-22N Specifications

| | |
|--|---|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Heat And Oil Resistant And Weather Resistant |
| Overall Width: | 0.500 Inches Nominal |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.032 Inches Nominal |
| Material Diameter: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.090 Inches Nominal |
| Loop Width: | 0.797 Inches Minimum And 0.827 Inches Maximum |
| Loop Length: | 1.360 Inches Minimum And 1.390 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.309 Inches Nominal |
| Material: | Aluminum Alloy 2024 Band |
| Material: | Rubber Chloroprene Class Cr Cushion |
| Material Document And Classification: | Qq-a-250/5,t4 Or T42 Fed Spec Single Material Response Band And Ams 3209 Cushion Assn Std Single Material Response Band |
| Style Designator: | Rectangular |

How to Order

Order this loop cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712D13-22N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.