

Description

Diameter: 13/64", rubber chloroprene class cr cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1712D1610N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-217-2264
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013120, Aluminum Article Noi Sub 6

NO IMAGE
AVAILABLE

P/N NAS1712D16-10N Specifications

Tongue Hole Type:	Round, Unthreaded
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.684 Inches Minimum And 0.744 Inches Maximum
Loop Width:	0.985 Inches Minimum And 1.015 Inches Maximum
Loop Length:	0.610 Inches Minimum And 0.640 Inches Maximum
Distance From Loop Center To Tongue End:	0.903 Inches Minimum And 0.963 Inches Maximum
Material:	Aluminum Alloy 2024 Band
Material:	Rubber Chloroprene Class Cr Cushion
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5,t4 Fed Spec Single Material Response Or Qq-a-250/5,t42 Fed Spec Single Material Response Band
Style Designator:	Rectangular
Specification/standard Data:	80205-nas1712 Professional/industrial Association Standard

How to Order

Order this loop cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712D16-10N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.