

P/N NAS1712D16-21N

Description

Diameter: 13/64", rubber chloroprene class cr cushion

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1712D1621N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-216-9110
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi



^{*} See page 2 for technical characteristics

P/N NAS1712D16-21N Specifications

Tongue Hole Type:	Round, Unthreaded
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.902 Inches Nominal
Loop Width:	0.985 Inches Minimum And 1.015 Inches Maximum
Loop Length:	1.298 Inches Minimum And 1.328 Inches Maximum
Distance From Loop Center To Tongue End:	1.121 Inches Nominal
Material:	Aluminum Alloy 1230 Band
Material:	Rubber Chloroprene Class Cr Cushion
Material Document And Classification:	Ams-3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5,alloy2024 Fed Spec Single Material Response Band
Style Designator:	Rectangular
Specification/standard Data:	80205-nas1712 Professional/industrial Association Standard

How to Order

Order this loop cushioned clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/NAS1712D16-21N and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/NAS1712D16-21N and selecting the