

P/N NAS1712D24-16T

Description

Diameter: 13/64", plastic polytetrafluoroethylene cushion

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS1712D2416T

Minimum Qty (MOQ): 5 EA

NSN: 5340-01-502-6305

Schedule B: 7616.99.5090

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi



^{*} See page 2 for technical characteristics

P/N NAS1712D24-16T Specifications

| Tongue Hole Type: | Round, Unthreaded |
|---|--|
| Overall Width: | 0.500 Inches Nominal |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 0.902 Inches Nominal |
| Loop Width: | 1.485 Inches Minimum And 1.515 Inches Maximum |
| Loop Length: | 1.985 Inches Minimum And 2.015 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.121 Inches Nominal |
| Material: | Aluminum Alloy 2024 Band |
| Material: | Plastic Polytetrafluoroethylene Cushion |
| Material Document And Classification: | Qq-a-250/5 Assn Std Single Material Response Band |
| Style Designator: | Rectangular |
| Specification/standard Data: | 80205-nas1712 Professional/industrial Association Standard |

How to Order

Order this loop cushioned clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/NAS1712D24-16T and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/NAS1712D24-16T and selecting the