

Description

Diameter: 13/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | NAS1712D3232N |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-00-480-9080 |
| Schedule B: | 7616.10.9090 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1712D32-32N Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Weather Resistant |
| Overall Width: | 0.500 Inches Nominal |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.402 Inches Nominal |
| Loop Width: | 1.985 Inches Minimum And 2.015 Inches Maximum |
| Loop Length: | 1.985 Inches Minimum And 2.015 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.621 Inches Nominal |
| Style Designator: | Rectangular |
| Specification/standard Data: | 80205-nas1712 Professional/industrial Association Standard |

How to Order

Order this loop cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712D32-32N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.