

Description

Diameter: 13/64", steel comp 302 band or steel comp 321 band or steel comp 304 band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1712D3232S
Minimum Qty (MOQ):	5
NSN:	5340-01-521-2931
Schedule B:	7616.10.9090
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS1712D32-32S Specifications

Tongue Hole Type:	Round, Unthreaded
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	2.402 Inches Nominal
Loop Width:	1.985 Inches Minimum And 2.015 Inches Maximum
Loop Length:	1.985 Inches Minimum And 2.015 Inches Maximum
Distance From Loop Center To Tongue End:	2.631 Inches Nominal
Material:	Rubber Chloroprene Class Cr Cushion
Material:	Steel Comp 302 Band Or Steel Comp 321 Band Or Steel Comp 304 Band
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Ams 5516 Assn Std 1st Material Response Band Or Ams 5510 Assn Std 2nd Material Response Band Or Ams 5513 Assn Std 3rd Material Response Band
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-35, Ty Vi Or Viii Fed Spec Single Treatment Response Overall
Style Designator:	Rectangular
Specification/standard Data:	80205-nas1712 Professional/industrial Association Standard

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712D32-32S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.