

Description

Diameter: 13/64", rubber chloroprene class cr cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1712D4438N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-286-9206
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013120, Aluminum Article Noi Sub 6



* See page 2 for technical characteristics

P/N NAS1712D44-38N Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Oil Resistant And Weather Resistant And Ozone Resistant And Heat
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.589 Inches Nominal
Loop Width:	2.735 Inches Minimum And 2.765 Inches Maximum
Loop Length:	2.360 Inches Minimum And 2.390 Inches Maximum
Distance From Loop Center To Tongue End:	1.808 Inches Nominal
Material:	Aluminum Alloy 2024 Band
Material:	Rubber Chloroprene Class Cr Cushion
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5,t4 Or T42 Fed Spec Single Material Response Band
Style Designator:	Rectangular
Specification/standard Data:	80205-nas1712 Professional/industrial Association Standard

How to Order

Order this loop cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712D44-38N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.