

## P/N NAS1712D48-18N

### **Description**

Diameter: 13/64", rubber chloroprene class cr cushion

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1712D4818N

Minimum Qty (MOQ): 5 EA

NSN: 5340-00-486-1211

Schedule B: 7616.10.1000

ECCN: 9A991

National Motor Freight: 013120, Aluminum Article Noi Sub 6



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1712D48-18N Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Weather Resistant
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.964 Inches Nominal
Loop Width:	2.985 Inches Minimum And 3.015 Inches Maximum
Loop Length:	1.110 Inches Minimum And 1.140 Inches Maximum
Distance From Loop Center To Tongue End:	1.183 Inches Nominal
Material:	Aluminum Alloy 2024 Band
Material:	Rubber Chloroprene Class Cr Cushion
Style Designator:	Rectangular
Specification/standard Data:	80205-nas1712 Professional/industrial Association Standard

## **How to Order**

Order this loop cushioned clamp from our inventory online by visiting <a href="https://military-fasteners.com/clamps/loop+clamps/NAS1712D48-18N">https://military-fasteners.com/clamps/loop+clamps/NAS1712D48-18N</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/clamps/loop+clamps/NAS1712D48-18N">https://military-fasteners.com/clamps/loop+clamps/NAS1712D48-18N</a> and selecting the