

P/N NAS1712D7-13N

Description

Diameter: 13/64", rubber chloroprene class cr cushion

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1712D713N

Minimum Qty (MOQ): 10 EA

NSN: 5340-01-032-3973

Schedule B: 7616.99.5090

ECCN: EAR99

National Motor Freight: 093880, Catches / Latches Metal Noi



^{*} See page 2 for technical characteristics

P/N NAS1712D7-13N Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Weather Resistant
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.808 Inches Nominal
Loop Width:	0.423 Inches Minimum And 0.453 Inches Maximum
Loop Length:	0.797 Inches Minimum And 0.827 Inches Maximum
Distance From Loop Center To Tongue End:	1.027 Inches Nominal
Material:	Aluminum Alloy 2024 Band
Material:	Rubber Chloroprene Class Cr Cushion
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5 T4 Or T42 Fed Spec Single Material Response Band
Style Designator:	Rectangular
Specification/standard Data:	80205-nas1712 Professional/industrial Association Standard

How to Order

Order this loop cushioned clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/NAS1712D7-13N and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/NAS1712D7-13N and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/NAS1712D7-13N and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/NAS1712D7-13N and selecting the quantity you want then click "add to cart".