

Description

Diameter: 13/64", asbestos cushion and plastic polytetrafluoroethylene cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|------------------------------------|
| SKU / Model: | NAS1712D816T |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-01-125-1385 |
| Schedule B: | 7616.10.9090 |
| ECCN: | 9A991 |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |



* See page 2 for technical characteristics

P/N NAS1712D8-16T Specifications

| | |
|--|---|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Weather Resistant |
| Overall Width: | 0.500 Inches Nominal |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 0.902 Inches Nominal |
| Loop Width: | 0.485 Inches Minimum And 0.515 Inches Maximum |
| Loop Length: | 0.985 Inches Minimum And 1.015 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.121 Inches Nominal |
| Material: | Aluminum Alloy 2024 Band |
| Material: | Asbestos Cushion And Plastic Polytetrafluoroethylene Cushion |
| Material Document And Classification: | Ams 3840 Assn Std Single Material Response Cushion |
| Material Document And Classification: | Qq-a-250/5,t4 Fed Spec Single Material Response Band Or Qq-a-250/5,t42 Fed Spec Single Material Response Band |
| Style Designator: | Rectangular |
| Specification/standard Data: | 80205-nas1712 Professional/industrial Association Standard |

How to Order

Order this loop cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712D8-16T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.