

**Description**

Diameter: 13/64", rubber chloroprene class cr cushion

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1712D818N
Minimum Qty (MOQ):	10
NSN:	5340-01-131-5579
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



\* See page 2 for technical characteristics

## P/N NAS1712D8-18N Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Cushioning Environmental Protection:</b>	Heat And Oil Resistant And Weather Resistant
<b>Overall Width:</b>	0.500 Inches Nominal
<b>Diameter:</b>	0.204 Inches Nominal
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	0.964 Inches Nominal
<b>Loop Width:</b>	0.485 Inches Minimum And 0.515 Inches Maximum
<b>Loop Length:</b>	1.110 Inches Minimum And 1.140 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	1.183 Inches Nominal
<b>Material:</b>	Aluminum Alloy 2024 Band
<b>Material:</b>	Rubber Chloroprene Class Cr Cushion
<b>Material Document And Classification:</b>	Ams 3209 Assn Std Single Material Response Cushion
<b>Material Document And Classification:</b>	Qq-a-250/5,t4 Fed Spec Single Material Response Band Or Qq-a-250/5,t42 Fed Spec Single Material Response Band
<b>Style Designator:</b>	Rectangular
<b>Specification/standard Data:</b>	80205-nas1712 Professional/industrial Association Standard

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1712D8-18N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.