

P/N NAS1712D8-32N

Description

Diameter: 13/64", rubber chloroprene class cr cushion

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS1712D832N

Minimum Qty (MOQ): 10 EA

NSN: 5340-01-133-9610

Schedule B: 7616.10.9090

ECCN: 9A991

National Motor Freight: 013120, Aluminum Article Noi Sub 6



^{*} See page 2 for technical characteristics

P/N NAS1712D8-32N Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Heat And Oil Resistant And Weather Resistant
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.402 Inches Nominal
Loop Width:	0.485 Inches Minimum And 0.515 Inches Maximum
Loop Length:	1.985 Inches Minimum And 2.015 Inches Maximum
Distance From Loop Center To Tongue End:	1.621 Inches Nominal
Material:	Aluminum Alloy 2024 Band
Material:	Rubber Chloroprene Class Cr Cushion
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5,t4 Fed Spec Single Material Response Band Or Qq-a-250/5,t42 Fed Spec Single Material Response Band
Style Designator:	Rectangular
Specification/standard Data:	80205-nas1712 Professional/industrial Association Standard

How to Order

Order this loop cushioned clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/NAS1712D8-32N and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/NAS1712D8-32N and selecting the