

Description

Diameter: 13/64", steel comp 302 band or steel corrosion resisting band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1713C10N
Minimum Qty (MOQ):	10 EA
NSN:	5340-01-042-3355
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N NAS1713C10N Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Weather Resistant
Overall Width:	0.470 Inches Minimum And 0.530 Inches Maximum
Diameter:	0.204 Inches Nominal
Material Thickness:	0.040 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.707 Inches Minimum And 0.737 Inches Maximum
Distance From Loop Center To Tongue End:	0.926 Inches Minimum And 0.956 Inches Maximum
Loop Inside Diameter:	0.610 Inches Minimum And 0.640 Inches Maximum
Material:	Rubber Chloroprene Class Cr Cushion
Material:	Steel Comp 302 Band Or Steel Corrosion Resisting Band
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Mil-s-5059 Mil Spec 1st Material Response Band Or Mil-s-6721 Mil Spec 2nd Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Center Mount
Specification/standard Data:	80205-nas1713 Professional/industrial Association Standard

How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1713C10N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.