

## **P/N NAS1713C18K**

### **Description**

Diameter: 13/64", steel comp 302 band or steel comp 321 band

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS1713C18K
Minimum Qty (MOQ):	10 EA
NSN:	5340-01-134-0874
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1713C18K Specifications**

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Heat
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.051 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.037 Inches Minimum And 1.067 Inches Maximum
Distance From Loop Center To Tongue End:	1.271 Inches Nominal
Loop Inside Diameter:	1.110 Inches Minimum And 1.140 Inches Maximum
Material:	Plastic Polytetrafluoroethylene Cushion
Material:	Steel Comp 302 Band Or Steel Comp 321 Band
Material Document And Classification:	Ams 3651 Assn Std Single Material Response Cushion
Material Document And Classification:	Mil-s-5059 Mil Spec 1st Material Response Band Or Mil-s-6721 Mil Spec 2nd Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Center Mount
Specification/standard Data:	80205-nas1713 Professional/industrial Association Standard

## **How to Order**

Order this cushioned loop clamp from our inventory online by visiting <a href="https://military-fasteners.com/clamps/loop+clamps/NAS1713C18K">https://military-fasteners.com/clamps/loop+clamps/NAS1713C18K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.