

Description

Cushioned Loop Clamp part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1713C40N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-242-3310
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N NAS1713C40N Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Heat And Oil Resistant And Weather Resistant
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.051 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.725 Inches Minimum And 1.755 Inches Maximum
Distance From Loop Center To Tongue End:	1.959 Inches Nominal
Loop Inside Diameter:	2.485 Inches Minimum And 2.515 Inches Maximum
Material:	Rubber Chloroprene Class Cr Cushion
Material:	Steel Corrosion Resisting Band
Material Document And Classification:	Ams3209 Mil Spec Single Material Response Cushion
Material Document And Classification:	Mil-s-5059 Mil Spec 1st Material Response Band Or Mil-s-6721 Mil Spec 2nd Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Mil Spec Single Treatment Response Band
Style Designator:	Center Mount
Specification/standard Data:	80205-nas1713 Professional/industrial Association Specification

How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1713C40N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.