

Description

Diameter: 13/64", steel comp 302 band or steel comp 321 band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | NAS1714C38K |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5340-01-397-0395 |
| Schedule B: | 7318.15.2091 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi |

NO IMAGE
AVAILABLE

P/N NAS1714C3-8K Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Overall Width: | 0.500 Inches Nominal |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.062 Inches Minimum And 0.077 Inches Maximum |
| Center To Center Distance Between Loop And Mounting Hole: | 1.902 Inches Nominal |
| Loop Width: | 0.500 Inches Nominal |
| Loop Length: | 1.500 Inches Nominal |
| Distance From Loop Center To Tongue End: | 2.121 Inches Nominal |
| Material: | Plastic Polytetrafluoroethylene Cushion |
| Material: | Steel Comp 302 Band Or Steel Comp 321 Band |
| Material Document And Classification: | Ams 3651 Assn Std Single Material Response Cushion |
| Material Document And Classification: | Mil-s-5059 Mil Spec 1st Material Response Band Or Mil-s-6721 Mil Spec 2nd Material Response Band |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Multiple Loop |
| Specification/standard Data: | 80205-nas1714 Professional/industrial Association Standard |

How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1714C3-8K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.