

P/N NAS1714D2-4NW

Description

Diameter: 13/64", asbestos cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1714D24NW

Minimum Qty (MOQ): 15 EA

NSN: 5340-01-154-4377

Schedule B: 7616.10.9090

ECCN: 9A991

National Motor Freight: 013120, Aluminum Article Noi Sub 6



^{*} See page 2 for technical characteristics

P/N NAS1714D2-4NW Specifications

| Tongue Hole Type: | Round, Unthreaded |
|---|---|
| Cushioning Environmental Protection: | Weather Resistant |
| Overall Width: | 0.500 Inches Nominal |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.031 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 0.652 Inches Nominal |
| Loop Width: | 0.235 Inches Minimum And 0.265 Inches Maximum |
| Loop Length: | 0.500 Inches Nominal |
| Distance From Loop Center To Tongue End: | 0.871 Inches Nominal |
| Material: | Aluminum Alloy 2024 Band |
| Material: | Asbestos Cushion |
| Material Document And Classification: | Ams 3840 Assn Std Single Material Response Cushion |
| Material Document And Classification: | Qq-a-250/5,t4 Fed Spec Single Material Response Band Or Qq-a-250/5,t42 Fed Spec Single Material Response Band |
| Style Designator: | Multiple Loop |
| Specification/standard Data: | 80205-nas1714 Professional/industrial Association Standard |

How to Order

Order this cushioned loop clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/NAS1714D2-4NW and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.