

## **P/N NAS1714D2-6NW**

### **Description**

Diameter: 13/64", rubber chloroprene class cr cushion

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1714D26NW

Minimum Qty (MOQ): 10 EA

NSN: 5340-01-070-2343

Schedule B: 7616.10.9090

ECCN: 9A991

National Motor Freight: 013120, Aluminum Article Noi Sub 6



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1714D2-6NW Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Weather Resistant
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.031 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.762 Inches Minimum And 0.782 Inches Maximum
Loop Width:	0.375 Inches Nominal
Loop Length:	0.750 Inches Nominal
Distance From Loop Center To Tongue End:	0.981 Inches Minimum And 1.001 Inches Maximum
Material:	Aluminum Alloy 2024 Band
Material:	Rubber Chloroprene Class Cr Cushion
Material Document And Classification:	Qq-a-251/5 Temper T4 Or T42 Fed Spec Single Material Response Band
Style Designator:	Multiple Loop
Specification/standard Data:	80205-nas1714 Professional/industrial Association Standard

## **How to Order**

Order this cushioned loop clamp from our inventory online by visiting <a href="https://military-fasteners.com/clamps/loop+clamps/NAS1714D2-6NW">https://military-fasteners.com/clamps/loop+clamps/NAS1714D2-6NW</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.