

Description

Diameter: 13/64", rubber chloroprene class cr cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1714D29NW
Minimum Qty (MOQ):	10 EA
NSN:	5340-01-076-6682
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013120, Aluminum Article Noi Sub 6



* See page 2 for technical characteristics

P/N NAS1714D2-9NW Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Weather Resistant
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.051 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.037 Inches Minimum And 1.067 Inches Maximum
Loop Width:	0.562 Inches Nominal
Loop Length:	1.124 Inches Nominal
Distance From Loop Center To Tongue End:	1.256 Inches Minimum And 1.276 Inches Maximum
Material:	Aluminum Alloy 2024 Band
Material:	Rubber Chloroprene Class Cr Cushion
Material Document And Classification:	Ams3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5t4ort42 Fed Spec Single Material Response Band
Style Designator:	Multiple Loop
Specification/standard Data:	80205-nas1714 Professional/industrial Association Standard

How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1714D2-9NW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.