

Description

Diameter: 7/32", steel comp 321 overall

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1715C10KWX
Minimum Qty (MOQ):	5
NSN:	5340-01-423-2418
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

P/N NAS1715C10KW Specifications

Tongue Hole Type:	Round, Unthreaded
Overall Width:	0.5000 Inches Nominal
Diameter:	0.2130 Inches Minimum And 0.2230 Inches Maximum
Material Diameter:	0.0285 Inches Minimum And 0.0355 Inches Maximum
Center To Center Distance Between Loop And Mounting Hole:	0.7800 Inches Nominal
Distance From Loop Center To Tongue End:	0.9180 Inches Nominal
Loop Inside Diameter:	0.6100 Inches Minimum And 0.6400 Inches Maximum
Special Features:	The Item Has A Cushion Made Of Molded Polytetrafluoroethylene Per Astm 1457, Type 1
Material:	Steel Comp 321 Overall
Material Document And Classification:	Ams 5510 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Single Loop

How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715C10KW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.