

Description

Diameter: 7/32", steel comp 321 overall

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | NAS1715C10KWX |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5340-01-423-2418 |
| Schedule B: | 7318.29.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |



* See page 2 for technical characteristics

P/N NAS1715C10KWX Specifications

| | |
|--|---|
| Tongue Hole Type: | Round, Unthreaded |
| Overall Width: | 0.5000 Inches Nominal |
| Diameter: | 0.2130 Inches Minimum And 0.2230 Inches Maximum |
| Material Diameter: | 0.0285 Inches Minimum And 0.0355 Inches Maximum |
| Center To Center Distance Between Loop And Mounting Hole: | 0.7800 Inches Nominal |
| Distance From Loop Center To Tongue End: | 0.9180 Inches Nominal |
| Loop Inside Diameter: | 0.6100 Inches Minimum And 0.6400 Inches Maximum |
| Special Features: | The Item Has A Cushion Made Of Molded Polytetrafluoroethylene Per Astm 1457, Type 1 |
| Material: | Steel Comp 321 Overall |
| Material Document And Classification: | Ams 5510 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Style Designator: | Single Loop |

How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715C10KWX> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.