

Description

Diameter: 13/64", steel comp 302 band or steel comp 321 bandplastic polytetrafluoroethylene cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1715C12KW
Minimum Qty (MOQ):	5
NSN:	5340-01-352-1230
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N NAS1715C12KW Specifications

Tongue Hole Type:	Round, Unthreaded
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.051 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.850 Inches Minimum And 0.880 Inches Maximum
Distance From Loop Center To Tongue End:	1.069 Inches Nominal
Loop Inside Diameter:	0.735 Inches Minimum And 0.765 Inches Maximum
Material:	Steel Comp 302 Band Or Steel Comp 321 Bandplastic Polytetrafluoroethylene Cushion
Material Document And Classification:	Mil-s-5059 Mil Spec 1st Material Response Band Or Mil-s-6721 Mil Spec 2nd Material Response Bandams 3651 Assn Std Single Material Response Cushion
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Offset Mount
Specification/standard Data:	80205-nas1715 Professional/industrial Association Standard

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715C12KW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.