

Description

Diameter: 13/64", steel comp 321 band or steel comp 347 band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | NAS1715C13KWX |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5340-01-099-8158 |
| Schedule B: | 7318.15.2091 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

P/N NAS1715C13KWX Specifications

| | |
|--|---|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Heat |
| Overall Width: | 0.500 Inches Nominal |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.0285 Inches Minimum And 0.0355 Inches Maximum |
| Center To Center Distance Between Loop And Mounting Hole: | 0.858 Inches Nominal |
| Distance From Loop Center To Tongue End: | 1.076 Inches Nominal |
| Loop Inside Diameter: | 0.798 Inches Minimum And 0.828 Inches Maximum |
| Material: | Steel Comp 321 Band Or Steel Comp 347 Band |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715C13KWX> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.